

StormPod[®]

modular stormwater filtration system

Sizes, Configurations and Installation

The StormPod is an economical, yet highly effective catch basin insert that utilizes Fabco's proprietary filter cartridges to capture sediments, trash and other debris in storm water runoff.

The StormPod uses a **factory-sized** mounting shroud to fit round grates starting at 24" through 30" (optional adaptor plates are available for sizes greater than 30") and square sizes from 24" to 26". No adjustments or modifications are required by the installer.



All standard StormPod units are shipped fully assembled and include one (1) replaceable filtering cartridge.

Tools required (not including any mandated safety devices): Grate lifter, sweeping broom, trash bags, and a 1" steel paint scraper.

Installation process

Note: installations should be done by qualified personnel only

- 1) If the StormPod is being installed in an area with vehicle traffic please be sure to follow proper safety precautions as prescribed by Local and State transportation agencies.
- 2) Prepare the site for installation by sweeping away any debris and loose sediments from around the selected storm sewer
- 3) Remove the storm sewer grate and place it next to the drain
- 4) Using a hand broom and/or scraper, remove loose debris from the support ledge beneath the grate. The StormPod will hang from this ledge when the installation is complete.



- 5) Lower the completed StormPod into position on the grate ledge. Make sure the StormPod mounting shroud sits firmly on the ledge. The mounting shroud should have a snug fit with less than 1/4" total clearance.



- 6) Replace the grate to complete the installation
- 7) Contact Fabco Industries Inc, Customer service with any questions on proper installation. Tel: (631)393-6024, Fax: (631) 501-5528, email: johnm@fabco-industries.com