



Configurations, sizes and specifications

StormPod stormwater filters, adapt Fabco's StormBasins advanced feature set including injection molded basin, replaceable filter cartridges, and covered bypass to a single size mounting system designed for round and square drain inlets.

StormPod (Square) Grates:

 <p>Requires 22" x 22" Min clear space Inside frame dimension</p>	Part number	9734-2A	9734-2B ²	9734-2S ²
	Flange/Grate Size	24" x 24"	26" x 26"	24" < X < 26"
	Number of Cartridges	1	1	1
	Filtered Flow Rate	115 gpm ¹	115 gpm ¹	115 gpm ¹
	Bypass Flow Rate	920 gpm	920 gpm	920 gpm
	Debris Capacity	2.1 ft ³	2.1 ft ³	2.1 ft ³
	Dia. plastic basin	19.5" Dia.	19.5" Dia.	19.5" Dia.
	Min. Depth Under Grate	26"	26"	26"
¹ Standard Cartridge P/N 9718-1 ² Contact Fabco sales for additional fitting requirements				

StormPod (Round) Grates:

 <p>Requires 22" dia. Min Clear Space Inside frame dimension</p> <p>Contact Fabco sales For minimum clear space requirements for 26", 28" and 30" products</p>	Part number	9734-1A	9734-1B	9734-1C	9734-1D
	Flange/Grate Size	24" Dia.	26" Dia.	28" Dia.	30" Dia.
	Number of Cartridges	1	1	1	1
	Filtered Flow Rate	115 gpm ¹	115 gpm ¹	115 gpm ¹	115 gpm ¹
	Bypass Flow Rate	920 gpm	920 gpm	920 gpm	gpm
	Debris Capacity	1.9 ft ³	2.7 ft ³	3.6 ft ³	4.7 ft ³
	Dia. plastic basin	19.5" Dia.	19.5" Dia.	19.5" Dia.	19.5" Dia.
	Min. Depth Under Grate	26"	29"	32"	35"
¹ Standard Cartridge P/N 9718-1					

Mounting system	Single sized Hybrid: Plastic shroud with metal support ring or frame
Plastic (debris) basin	Plastic Co-polymer; 0.25" thickness; 19.5" dia.; 1 cartridge port with twist lock mech.
Available cartridges	Gen Purpose, High Flow, Bacteria, Nutrient, Heavy Metal, Short depth, other comb.
Weight w/o cartridge	Approx. 20 lbs