



StormBasin Specification Sheet

Product No.: 9730-1A-000

(Page 1 of 2)

Physical Properties:

1. Weight (empty): 50 lb max
2. Material:
 - a. Adjustable Flange and Deflector: Aluminum Alloy 6063-T6
 - b. StormBasin: Polypropylene Polyethylene Impact Copolymer (Nucleated)
 - c. Corner Fill: Neoprene Rubber, 80 Durometer
 - d. Support Hardware: CRES 300 Series
3. Performance Characteristics (typ):
 - a. Debris Capacity: 4.0 cu-ft
 - b. Filtered Flow Rate w/standard cartridges: 230 gpm (0.51 cfs)
 - c. Bypass Flow Rate: 1417 gpm (2.7 cfs)
4. Clear Opening Range (0.5 increments):
 - a. Minimum Size: 19.0 X 45.0
 - b. Maximum Size: 24.0 X 50.0



StormBasin Specification Sheet

Product No.: 9730-1A-000

(Page 2 of 2)

Mechanical Properties:

Basin/Flange Assembly:

1. Aluminum Alloy 6063-T6
 - a. Yield Strength: 40,000-Psi
 - b. Tensile Strength: 45,000-Psi
 - c. Shear Strength: 30,000-Psi
2. Co-Polymer (Injection Molded):
 - a. Tensile Strength: 3,200-Psi
 - b. Heat Deflection Temperature (@66-Psi): 175°F
 - c. Notched IZOD Impact Strength (@73°F): No Break
3. Hardware: CRES 300 Series